

## GO-SOUND 12A 880 WATT 12" POLYPROPYLENE ACTIVE SPEAKER

Go-Sound series is built with the user in mind. As result of years of experience gathered by Soundsation in portable sound systems, we designed these versatile high-quality speakers with unmatched value and performances. Built in a polypropylene cabinet, sturdy yet compact and lightweight, these active speaker are equipped with Class AB amplifiers, which guarantee reliability and outstanding performances. Mic and line inputs are included to allow the user to connect various audio sources such as microphones, mixers as well as smartphones and tablets.Go-Sound series is an incredible value and the perfect solution in many situations such as parties, presentations, schools, conference and live music, delivering great sound quality, reliability and ease of use.









## **PRODUCT DETAILS**

## **KEY FEATURES**

2-Way Active Speaker

Sturdy polypropylene enclosure yet compact and lightweight

880 Watt class AB power amplifier

12" woofer with 1.35" compression driver

Balanced microphone/Line inputs XLR + ¼" Jack, line inputs Stereo RCA + XLR, line input stereo Mini jack ideal to connect smartphones and tablets

XLR line output

Mic/line switch, volume and equalizer (Hi and Low) controls

36 mm standard pole mount

2 side handles and 1 on top for convenient carrying

Speaker Dimension (WxHxD): 375 x 588 x 320 mm

Weight: 12,2 Kg





## **SPECIFICATIONS**

|                             | 2-Way active speaker                             |
|-----------------------------|--|
| Woofer                      | 12" with 2" voice coil                           |
| Compression driver          | 1.35" voice coil, 1" throat                      |
| Directivity                 | 90° x 50°, asymmetric                            |
| Frequency Response [- 3dB]  | 60Hz - 18KHz                                     |
| Frequency Response [- 10dB] | 55Hz - 18KHz                                     |
| Max SPL(Peak)               | 114dB  |
| Sensitivity                 | 94dB   |
|                             | Class AB amplifier                               |
| Power (Peak/Rated)          | 880W/440W  |
| Crossover                   | 3KHz, 24dB/Oct.                                  |
| EQ                          | High (2.5KHz, +/- 12 dB); Low (150Hz, +/- 12 dB) |
| LEDs                        | Power On (Green), Clip (Red)                     |
| Power Requirement           | 230Vac - 50 Hz                                   |
| Minimum Power Consumption   | 230W   |
| Power Connector             | VDE with T3.15A-250V Fuse                        |
| Speaker Dimension (WxHxD)   | 375 x 588 x 320 mm                               |
| Weight                      | 12,2 Kg  |

