



## PRODUCT DETAILS

### KEY FEATURES

24 bit Processor with 24 bit DELTA-SIGMA converters

Built-in Effects : REVERB, DELAY, CHORUS, ROTARY, PITCH SHIFTER and combined FX (CHR/FLG+REVERB, DELAY+REVERB, CHR/FLG+DELAY)

Advanced MIX system: (INPUT-OUTPUT-MIX)

Wide LCD screen for an optimal check of the status of the unit

Ultra-rugged construction allowing to use the unit in Live performances

Software manager for remote unit controlling included

## SPECIFICATIONS

<b>24 Bit Processing</b>	
<b>Converters</b>	24-Bit Delta-Sigma, 128-times oversampling
<b>Sampling Rate</b>	48 KHz
<b>Inputs</b>	Balanced XLR & JACK TRS
<b>Input Max Level</b>	+15 dBu
<b>Input impedance</b>	approx. 30 KOhm
<b>Outputs</b>	Balanced XLR & JACK TRS
<b>Output Max Level</b>	+21 dBu
<b>Output Impedance</b>	approx. 150 Ohm
<b>Foot Switch Input</b>	TS Jack
<b>MIDI connection</b>	2 x DIN 5 pin
<b>USB connection</b>	USB Connector type "A"
<b>Frequency Response</b>	10 Hz to 22 kHz, -3 dB
<b>Dynamic range</b>	103 dB, 10 Hz to 22 kHz A-Weighted
<b>THD</b>	0,01 % typ. @ 0 dBFS
<b>Crosstalk</b>	-75 dB @ 1 kHz
<b>Signal-to-noise Ratio</b>	10 Hz to 22 kHz >100 dB @ 0 dBu, A-weighted
<b>Power consumption</b>	approx. 15 W