

## HYPERUP 8A

# PORTABLE COLUMN SPEAKER WITH DSP, BLUETOOTH AND TWS

There are so many small sound reinforcement applications where is not required a huge sound pressure like a rock concert, but where frequency response and sound definition are crucial. However, the available space is often limited. Additionally, correct loudspeaker positioning is often overlooked, which can negatively impact the final result. The Soundsation HyperUp 8A is a solution to these challenges.



This is a portable sound system that weighs just under 12kg. It features an 8-inch high-excursion subwoofer and a vertical array of four 2.75-inch full-range speakers. The speakers are driven by 600W peak class-D power amplifiers and digital processing, which allows for total control of transducers, multi-band limiter, protections, and frequency response. The system also includes a 3-channel mixer with USB, SD-Card, and Bluetooth connectivity. The DSP is user-friendly and offers four presets to accommodate different needs: Flat, Music, Band, and Speech.

The system has an HF coverage of 120° (H) x 20° (V). Its column structure is divided into three segments, with a maximum height of approximately 1.85m including the subwoofer. This design allows for flexible placement of the mid-high transducers, depending on whether the system is on the floor, on a stage, or at a height where the passive segments are not required.

The subwoofer is internally connected to the column, resulting in an elegant and minimalist aesthetic. The only visible cables are the power and audio connection at the back. Additionally, using Bluetooth to connect to your audio source further reduces the need for cables.

In the case of a dual HyperUp 8A stereo system, the TWS (True Wireless Stereo) connection can be invisible. This system enables wireless connection between two HyperUp speakers, allowing the 'master' (the one to which the Bluetooth audio sources is connected) to connect to the 'slave' so that the latter only plays the right channel. This creates a stereo system without the need for audio connections between the two. The system includes a padded bag for transporting the three column segments safely. An optional subwoofer cover (HyperUp 8 Sub Cover, part number SOU0114) is also available.





## HIGHLIGHTS



### GO-SOUND AIR CONTROL APP

Nowadays, our tablets and mobile phones have become the primary tools for music, parties, and other occasions. Some of the latest devices no longer have an analogue output, which means that they require adapters (often bulky and expensive) or Bluetooth interfaces to connect to normal audio speakers. HyperUp Air's Digital Media Player provides solutions to these and many other needs. In addition to the standard Bluetooth connection and USB/SD-Card slots, the player's functions can be controlled through the free Go-Sound Air app for Android and iOS, directly from a tablet or smartphone.

### TRUE WIRELESS STEREO (TWS)

HyperUp column speakers feature a multi-channel Bluetooth system. This technology, in addition to offering one stereo channel for normal connection of Bluetooth audio sources (such as mobile phones, tablets, computers, etc.) and a second channel for control via the Go-Sound Air App for Android® and iOS®, has an additional third channel for the True Wireless Stereo.

This function allows wireless connection between identical speakers so that the "master" - that is, the one to which the Bluetooth audio source is connected (your phone or tablet, etc.) - connects to the "slave" and the latter plays only the right channel of the audio source (in this case the master will play only the left channel). This provides a true stereo system without the need for any audio connections among the Bluetooth audio source, the master and the slave HyperUp speakers.





## CONVENIENCE AND COMPACTNESS

HyperUp is a lightweight and practical system that can be assembled in just a few minutes. It has a neat and minimalist look. Its compact dimensions make it the ideal companion in situations where space is at a premium or a pleasant and discreet visual impact is desired. The subwoofer occupies a space of about 30x40cm.

---

## WIDE HORIZONTAL COVERAGE

Thanks to the arrangement of full-range transducers inside the column, HyperUp offers a wide horizontal angular coverage of 120°. This results in a homogeneous and distributed coverage of the audience, making it ideal for both mono and stereo use. Because of the limited vertical coverage (20°), column segments without speakers can be added or removed from the column to compensate for limited coverage. This depends on the position of the audience (seated/standing) and the subwoofer's position (on the ground or above a stage).



## PRODUCT DETAILS

### KEY FEATURES

4x 2.5" Wideband Speakers

120° H x 20° V Coverage

1x 8" Woofer with 2" Voice Coil

600W Peak Power, Class-D Power Amp

2x Mic-Line Inputs with Combo Connector

1x Stereo Line Input with RCA & Mini-Jack

DSP with 4 Presets

Bluetooth with TWS Function (True Wireless Stereo)

## SPECIFICATIONS

<b>Speaker Type</b>	8" Portable Column PA System with Mobile App
<b>Frequency response</b>	50Hz-20kHz
<b>Input Sensitivity</b>	0dBu (selectable)
<b>Sensitivity (1W/1m)</b>	95 dB
<b>Max. SPL</b>	121 dB
<b>Amp. Max. (Program/Peak)</b>	200W/600W - 2 x Class-D
<b>Protection System</b>	DSP based multiband limiter, Short-Circuit, Over Current, Overheating
<b>LF</b>	8" - 4 ohm
<b>Vertical Array System</b>	4x 2.5" Wideband Speakers
<b>Directivity (HxV)</b>	120° x 20°
<b>Crossover</b>	250Hz - 24dB/oct.
<b>Connections</b>	2x Mic/Line Combo (XLR/Jack 6.35mm), Stereo Mini Jack, RCA Jack, USB-SD-Bluetooth, XLR Mix Out,
<b>Controls</b>	2x Mic/Line level, Aux In Level (Aux/BT/USB/SD level), Media Player Buttons, Master level, DSP Preset, Front LED
<b>LED Indicators</b>	Limit, DSP Preset
<b>Media player</b>	USB, SD-Card, Bluetooth, LCD Display, Remote Control
<b>Media player controls</b>	Mode, Previous track, Next track, Loop, Play/Pause
<b>App Control</b>	Auxiliary BT connection to Go-Sound Air App for Android®/iOS®
<b>Mains Power</b>	100-240Vac - 50/60Hz
<b>Fuse</b>	T1.60AL/250V
<b>Mains Connector</b>	VDE with Fuse
<b>Housing / Grille material</b>	Sub - PP / Column - PP / Grille - Steel
<b>Handles</b>	1 Handle on top
<b>Accessories</b>	Column Padded Bag (Included), Subwoofer Cover (Optional)

<b>Column Dimension (WxHxD)</b>	77 x 515 x 74 mm
<b>Subwoofer Dimension (WxHxD)</b>	293 x 455 x 380 mm
<b>Packing Dimension (WxHxD)</b>	545 x 570 x 355 mm
<b>Column Net Weight</b>	1,7 kg (segment with speakers), 0,85 kg (segment without speakers)
<b>Subwoofer Net Weight</b>	8,6 kg
<b>System Net Weight</b>	11.8 kg
<b>Gross Weight</b>	13,8 kg