

BLUEPORT FX

2X100W PORTABLE PA SYSTEM WITH ACTIVE MIXER AND TWO PASSIVE 2-WAY SPEAKERS

BLUEPORT FX is the result of years of experience gathered by SOUNDSATION in Portable Sound systems, a segment where quality, versatility and value for money are absolutely essential. This active amplified portable PA system includes two passive speakers with 10 "woofers and integrated amplified mixer. In addition to the MP3 player with USB, SD card and Bluetooth TM, the system integrates a 24Bit DSP FX with 16 genuine effects to add to the MIC inputs choosing the level for each channel. The integrated mixer is equipped with a Class-D 2x100W (RMS) amplifier. The enclosures (ABS) are strong and lightweight and have a pleasant look.























PRODUCT DETAILS

KEY FEATURES

Two passive speakers with integrated amplified mixer

Class-D 2x100W (RMS) Amplifier

Speakers with 10" Woofers and 1" compression driver

Dual Band Equalizer (Low/High frequencies)

MP3 player with USB, SD card and Bluetooth™

4 Microphones/Line Inputs

1 Stereo RCA/JACK 1/4" Line Input

1 Stereo RCA Line Output

24Bit DSP FX with 16 genuine effects

Infrared receiver for remote control

35 mm hole for pole mounting

Sturdy, compact and lightweight cabinets (ABS)





SPECIFICATIONS

SPECIFICATIONS	
	Frequency Response - 65 Hz - 20KHz [- 10dB] ; 65Hz-19KHz [- 3dB]
	System Max SPL / Sensitivity - 118dB / 95dB
	HF Type - Compression Driver; Throat diameter / Voice coil diameter - 1" / 1"; Driver throat diameter - 80mm; Directivity (HxV) / Horn Type - 90°x40°-60° / Asymmetric; Magnet Material / Weight - Ferrite Magnet Structure / 225g; RMS Power - 25W; Sensitivity(1W/1m) - 106dB; Crossover Frequency / Filter Slope - 3KHz / 6dB/Octave; Impedance - 8 Ohm
	LF Woofer Diameter - 10"; Voice coil diameter - 10"; Voice coil diameter - 1.5"; Magnet Material / Weight - Ferrite Magnet Structure / 677.3g; RMS Power - 100W; Frequency Response - 63Hz - 3.5KHz; Max SPL (1W/1m) - 94dB; Impedance - 4 Ohm
	Amplifier Class - D ; Power RMS / Peak - 2 x 100W / 2 x 250W ; Output Connectors - 2x 1/4" Jack
	Input Channels - 4 Mic/Line + 1 Stereo Line
	Phantom Power - (CH1-4) +48V
EQ High (CH 1-4 and Master) - Cut-off freq	1KHz / Gain
EQ Low (CH 1-4 and Master) - Cut-off freq	500Hz / Gain
	Digital Effects - 16 Presets with Level Control (CH1-4)
	Digital Multimedia Player - USB, SD-CARD and Bluetooth
	Power Requirement - 230Vac-50Hz ; Power Consumption - 350W ; Power Switch - YES ; Connector - VDE ; Fuse - T3.15A - 250V
	Speaker Housing material - ABS
	Grille material / thickness - Steel / 0.8 mm
	Mixer Housing material - ABS
	Handles -YES
	Pole Mount - YES/35mm
	Single Speaker Size (WxHxD) - 330 x 300 x 490mm





Packing Size (WxHxD) - 640 x 365 x 545mm
Net Weight (2 speakers + mixer + accessories) - 16kg
Gross Weight - 18Kg

