

VISAGE-C01D BK

CARDIOIDE HEADSET MIC., 4-PIN MINI-XLR, BLACK, BLACK (SHURE® TYPE)


Soundsation Visage C01 Headset microphone is the right balance between elegance, flexibility, discretion and strength. It allows singers, musicians, actors, public speakers, broadcast professionals, to **move freely** during their performance and always guarantee an accurate capture of the voice.

The frequency response and the excellent **plosive attenuation**, allow you to obtain a warm and sparkling sound, without unnatural emphasis.













PRODUCT DETAILS

KEY FEATURES

Back-electret high-performance capsule for professional audio quality

Designed for withstand very close sound sources (provides off-axis rejection to high SPL sounds)

Cardioid pattern for accurate voice capture and minimum room noise

Waterproof selected material for maximum duration in any application

Microphone arm and cable are easily attached to frame

Special rubber material ear-set for perfect adherence to ear shape

Left or right microphone placement according to user preference

Available in Black or Beige

4-Pin Mini-XLR Connector (SHURE®)

Headset bag for better preserve the microphone

Color gift box for accurate storage and display





SPECIFICATIONS

| Element Back-Electret Capsule Directivity Unidirectional Frequency Range 45Hz~19.6kHz Sensitivity -46dBV(±3dB) Maximum SPL 125dB Output Impedance 200? Operation Voltage DC 1.5~9V Connector 4-Pin Mini-XLR (SHURE®)* - it includes a 2.2kohm resistor between pin 2 and 3 Cable Length 1.5m Color Black Headset Weight 28g Packing Size 162 x 122 x 54mm Packing Weight 190g | | |
|---|-------------------|-----------------------|
| Frequency Range 45Hz~19.6kHz Sensitivity -46dBV(±3dB) Maximum SPL 125dB Output Impedance 200? Operation Voltage DC 1.5~9V Connector 4-Pin Mini-XLR (SHURE®)* - it includes a 2.2kohm resistor between pin 2 and 3 Cable Length 1.5m Color Black Headset Weight 28g Packing Size 162 x 122 x 54mm | Element | Back-Electret Capsule |
| Sensitivity -46dBV(±3dB) Maximum SPL 125dB Output Impedance 200? Operation Voltage DC 1.5~9V Connector 4-Pin Mini-XLR (SHURE®)* - it includes a 2.2kohm resistor between pin 2 and 3 Cable Length 1.5m Color Black Headset Weight 28g Packing Size 162 x 122 x 54mm | Directivity | Unidirectional |
| Maximum SPL 125dB Output Impedance 200? Operation Voltage DC 1.5~9V Connector 4-Pin Mini-XLR (SHURE®)* - it includes a 2.2kohm resistor between pin 2 and 3 Cable Length 1.5m Color Black Headset Weight 28g Packing Size 162 x 122 x 54mm | Frequency Range | 45Hz~19.6kHz |
| Output Impedance 200? Operation Voltage DC 1.5~9V Connector 4-Pin Mini-XLR (SHURE®)* - it includes a 2.2kohm resistor between pin 2 and 3 Cable Length 1.5m Color Black Headset Weight 28g Packing Size 162 x 122 x 54mm | Sensitivity | -46dBV(±3dB) |
| Operation Voltage DC 1.5~9V Connector 4-Pin Mini-XLR (SHURE®)* - it includes a 2.2kohm resistor between pin 2 and 3 Cable Length 1.5m Color Black Headset Weight 28g Packing Size 162 x 122 x 54mm | Maximum SPL | 125dB |
| Connector 4-Pin Mini-XLR (SHURE®)* - it includes a 2.2kohm resistor between pin 2 and 3 Cable Length 1.5m Color Black Headset Weight 28g Packing Size 162 x 122 x 54mm | Output Impedance | 200? |
| Cable Length 1.5m Color Black Headset Weight 28g Packing Size 162 x 122 x 54mm | Operation Voltage | DC 1.5~9V |
| Color Black Headset Weight 28g Packing Size 162 x 122 x 54mm | Connector | |
| Headset Weight28gPacking Size162 x 122 x 54mm | Cable Length | 1.5m |
| Packing Size 162 x 122 x 54mm | Color | Black |
| | Headset Weight | 28g |
| Packing Weight 190g | Packing Size | 162 x 122 x 54mm |
| | Packing Weight | 190g |

