

WF-U2302PP

TRUE DIVERSITY DUAL WIRELESS MICROPHONE SYSTEM WITH 2 BODYPACK TRANSMITTERS AND HEADSET MICROPHONES 630-660MHZ

WF-U2302 is a dual UHF **True Diversity** professional wireless microphone with 300 channels for each microphone, and a simple and intuitive user interface.

“**True Diversity**” means that the receiving system is equipped with two antennas, two receiving circuits and a device capable of continuously choose the stronger and interference-free signal. This technology is used for both single systems (WF-U1300 Series) or dual systems (WF-U2302).

The WF-U2302 is built with leading technology that allows the integration of many of the major functions - such as amplification section, digital signal processing, PLL (Phase-Locked Loop) frequency synthesis, and more - into a single CHIP. This allows us to offer highly professional performance yet cost-effective products.

The WF-U2302 is also equipped with the automatic frequency search system and IR sync system for channel synchronization between receiver and transmitter in a quick way. Furthermore, the Digital Pilot Technology not only allows to monitor reception level and battery charge, but even to operate with multiple systems without problems.

Finally, there are two optional kit for rack mounting of 1 or 2 receivers, respectively, on 1 or 2 standard 19” rack units. Ask your dealer or visit SOUNDSATION website www.soundsationmusic.com for further details.



PRODUCT DETAILS

KEY FEATURES

UHF True Diversity Technology to avert Interferences

300 Preset Frequencies and IR Matching System for Quick Setup

630-660MHz UHF Band

Simple and Outright User Interface with LCD display on Transmitter and Receiver

Digital Pilot Technology to allow Multisystem Operation

Transmitter AF-level and Battery-Low Monitoring directly on the Receiver

80m Ideal Distance (without obstacles)

Bodypack with Connector Locking System

Professional and Lightweight Headset with High-Sensitivity Dynamic Cardioid Capsule

Half 19" Rack Unit with metal housing and removable antennas

Optional Rack-Mount Kits for 1 or 2 units

SPECIFICATIONS

Carrier Frequency	UHF 630-660 MHz
Dynamic Range	>90dB
Frequency Response	40Hz-15KHz \pm 3dB
Audio Output Level	Balanced 400mV; Unbalanced 400mV
Packing Dimensions (WxHxD)	435 x 104 x 321 mm
Packing Gross Weight	2.5 kg
Receiver Power Supply	DC 12V / 500mA
Consume Power	7W
Signal/Noise Ratio	>90dB
Receiving Sensitivity	5dBuV
Receiver Dimensions (WxHxD)	210 x 43 x 187 mm (antennas not incl.)
Antenna	max. 255 mm
Net Weight	0.53 kg
Transmitter Power	30mW (Max)
Modulation Type	FM
Battery Voltage	3V (2x1.5V AA Battery)
Continuous Using	5 hours
Pocket Transmitter Dimensions (WxHxD)	62 x 103 x 30 mm
Pocket Transmitter Antenna (W/DxH)	\varnothing 3 x 9 mm
Pocket Transmitter Net Weight	0.132 kg (batteries included)