

## AXIS IV MKII

# 4X32W RGBW LED 4 HEAD BEAM MOVING HEAD

When giving colors to your gigs passes through simplicity of use, portability and the benefits of modern LED technology, AXIS IV MKII becomes the reference to all musicians, DJs and entertainment operators.

AXIS IV MKII has been designed to be all-in-one system. This bar offers 4 moving heads able to swivel by up to 540° horizontally and 270° vertically, with extremely fast and accurate movements. It can be mounted on a truss and on lighting supports with Ø35mm pole, thanks to the supplied adapter. Each moving head mounts a 32W RGBW 4in1 LED with beam angle from 6° which ensures brilliant colors, high performance in terms of brightness and duration. Each head, also, can be controlled independently both in PAN/TILT movements and colors. Control modes are Sound, DMX Master/Slave, and Auto.

It is also available (optional) a professional flight case with wheels (2 with brake) for two bars (AXIS IV MKII CASE – SKU: J684J).



## PRODUCT DETAILS

### KEY FEATURES

Bar with four-head LED moving light (4pcs 32W RGBW 4in1)

Easy to control by LCD Graphic Display

6° Beam Angle

Light Lumen @ 1m from 24000 to 68000 LUX

Standalone Operation

Sound Control via built-in microphone

Master/Slave synchronization

DMX-512 protocol with 5 channel modes (6CH, 10CH, 19CH, 32CH and 56CH DMX)

2 bundled Fast lock Omega Brackets

Bundles Ø36mm Stand Adapter (stand not included)

## SPECIFICATIONS

<b>Light source</b>	4x 32W RGBW 4in1 LED
<b>Brightness @ 1m (single head)</b>	R 24000 Lux; G 50000 Lux; B 80000 lux; W 68000 lux
<b>Brightness @ 2m (single head)</b>	R 11500 lux; G 18000 Lux; B 27000 Lux; 26000 lux
<b>Colors</b>	RGBW with color mixing
<b>Beam corner</b>	6°
<b>Control mode</b>	DMX512, Master / Slave, Sound, Auto
<b>DMX mode</b>	6CH / 10CH / 19CH / 32CH / 56CH
<b>Power connectors</b>	PowerCon input / output
<b>DMX connectors</b>	In/Out XLR 5-Pin + In/Out XLR 3-Pin
<b>Display</b>	2.4 "TFT LCD
<b>Power supply</b>	110V ~ 240V - 50-60Hz
<b>Max Power Consumption</b>	200W
<b>Fuse</b>	F3AL / 250V (5x20mm)
<b>Bar size (WxDxH)</b>	1003.6 x 115 x 271.4 mm
<b>Bar weight</b>	11.5 kg
<b>Packaging dimensions (WxDxH)</b>	1090 x 180 x 360 mm
<b>Packaging Weight</b>	13.25 kg
<b>Accessories supplied</b>	1x power cable, 2x quick-lock omega-type brackets, Ø36mm pole adapter (stand not included)