

HYPER-PRO 10 PLUS


10" 2-WAY ACTIVE LOUDSPEAKER WITH DSP

The new Hyper-Pro Plus speakers represent a new important stage in the evolution of the famous **Hyper series** by Soundsation. The power, audio quality and convenience of the previous models are now integrated with the functions which are essential for those who professionally use a speaker as a work tool.

600W continuous **D-Class** amplifier (700W for 12" and 15" models), selected woofers and compression drivers, **DSP** for Crossover control, **EQ**, **2-Band Limiter**, **phase alignment** and **delay optimization** of woofers and compression drivers. All this technology can ensure high performance and maximum audio quality in any use conditions.

The control panel includes two XLR-Combo Mic/Line inputs, the Mix output and **4 Audio Programs** (Music, Live, Monitor, Vocal) to quickly adapt the speaker to the main uses.

The stylish and sturdy cabinet is designed to be installed vertically on the floor or on a 35mm pole/tripod, and also suspended horizontally or vertically thanks to the 4 M8 fixing points.



PRODUCT DETAILS

KEY FEATURES

2-way Loudspeaker, Bass-Reflex Design

600W Continuous / 1200W Peak Class-D amplifier

90°H x 60°V Coverage

DSP for Crossover, EQ and 2-Band Limiter Control, Phase and Time Optimization

4 EQ Presets (Music, Live, Monitor, Speech)

2 Mic-Line Combo Inputs and Balanced Mix Output

On-off key for the Front LED

35mm Adapter for Pole or Tripod Stand

4 Fixing Points for M8 Eyebolts

SPECIFICATIONS

System Type	2-Way Active 10" Loudspeaker, Bass-Reflex
Power Rating	600W Continuous, 1200W Peak
Frequency Response	60Hz-20kHz
Max SPL	128dB SPL
LF Driver	10" Custom Woofer
HF Driver	1" Compression Driver
Coverage	90°H x 60°V
Crossover Frequency	2.8kHz
Input Connectors	2x Balanced Combo XLR/1/4" Jack Connectors
Output Connectors	1x Balanced XLR Mix Output
Indicators	Power, Clip, Preset, Front Led
EQ	4 Presets (Music, Live, Monitor, Vocal)
DSP	Crossover, EQ, Dual Band Limiters, Phase and LF/HF Time Alignment
Controls	2x Channel Gain, Master Volume, Front Led On/Off, Ground Lift, EQ Preset
AC Power	100-120V~ or 220-240V~ 50/60Hz (User Selectable)
Power Consumption	315W Typical
Cabinet	Polypropylene
Handles	1 on Sides, 1 on Top
Monitor Angle	45°
Finish	Black
Grille	Powder-Coated Steel with Acoustic Foam
Pole-Mount	36mm Pole Socket
Flying Points	4x M8
Unit Size (WxDxH)	302 x 310 x 529 mm
Net Weight	11 Kg

Carton Size (WxDxH) 370 x 360 x 571 mm

Packed Weight 12.8Kg