

PROVIBE 8A

8" 2-WAY ACTIVE SPEAKERS WITH BLUETOOTH AND TWS

The ProVibe 8A is a compact active loudspeaker that combines Soundsation's signature style with professional features. It boasts an updated, elegant, and robust design.

The rear panel features a 3-channel mixer with Line/Mic inputs, Bluetooth input, 2-band EQ, and Mix out. Each channel has its own volume control. The TWS (True Wireless Stereo) function enables wireless connection between identical speakers, allowing the 'master' speaker, to which the Bluetooth audio source is connected, to connect to the 'slave' speaker, which only plays the right channel. This creates a stereo system without the need for audio connections between the two speakers.

The 8-inch woofer and 1-inch compression driver are powered by a Class AB amplifier with a peak power of up to 320W. The housing has an elegant and professional appearance and features a vented architecture with bass-reflex openings in the lower corners near the woofer. The symmetrical waveguide provides an angular coverage of 90° (H) x 60° (V). The back of the housing allows for horizontal use at angles of 45° and 25°, making it suitable for stage monitor applications. The housing also includes 3 M8 attachment points for suspended mounting and a 36mm hole for use on a pole or tripod.





HIGHLIGHTS



ELEGANCE, COMPACTNESS AND RELIABILITY. IN SHORT: PROVIDE!

Its purpose is not only to emit sounds and vibrations, but also to create music, convey emotions, exchange ideas, and promote knowledge. At Soundsation, we believe that ProVibe should align with contemporary aesthetic canons, characterized by essential and elegant lines. We believe that beauty should not compromise practicality or longevity. We have created a new range of active loudspeakers that take these concepts to a professional level, starting with simple vibration. In short: ProVibe!

ONE SOLUTION FOR MULTIPLE FORMATS

The 3-channel mixer is designed to address the common issue of adapting various input signals and connections from different sources. It can handle microphones, balanced and unbalanced line inputs, as well as XLR, 1/4" jack, RCA, and mini-jack connections without any level problems or the need for adapters.

The input preamplifiers are designed to accept input signals with a wide dynamic range, providing ample headroom to meet any sound reinforcement needs.



BLUETOOTH AND TWS



Nowadays, our devices are frequently used as the primary source of music at social events. Some modern devices no longer have an analogue output, necessitating the use of adapters (which can be bulky and costly) or Bluetooth interfaces.

ProVibe offers a solution to this issue. One of the mixer's three channels, which has independent volume control, is solely dedicated to receiving Bluetooth stereo audio signals. In addition, for two ProVibe speakers of the same type (e.g. two ProVibe 12A, or two ProVibe 15A, etc.), it is possible to wirelessly connect them to each other. This allows one speaker to play the left channel and the other to play the right channel of the same Bluetooth signal.

PRODUCT DETAILS

KEY FEATURES

2-Way Active Speaker

Sturdy and Stylish Polypropylene Housing

320W Peak Power

90°H x 60°V Directivity

3-Channel Mixer with Bluetooth

TWS (True Wireless Stereo) Function

36 mm standard pole mount

SPECIFICATIONS

Speaker Type	2-Way Active Speaker
Frequency Response [- 10dB]	80Hz - 20kHz
Max SPL	110 dB
Sensitivity	91 dB
Compression Driver	1"
Directivity (HxV)	90° x 60°
Crossover Frequency	3.5kHz
Woofer Diameter	8"
Amp Class	Class-AB
RMS Power	80W
Program/Peak Power	160W/320W
Input Connections	XLR + 1/4" Jack (Mic Line In), XLR + Stereo RCA + Stereo Mini jack (Line In)
Output Connections	XLR (Mix Out)
Mic/Line In Controls	Mic/Line switch and volume, Line In & Aux In volume
BT In	BT Pair/TWS button, Volume
LED Indicators	Power On (Green), Clip (Red), BT connected (Blue)
EQ	EQ High 2.5kHz-18kHz +/- 10dB; EQ Low 42Hz-150Hz +/- 10dB
Power Requirement	230Vac - 50 Hz
Power Consumption (Average)	90W
Housing material	Polypropylene
Flyable	Yes
Handles	1 on top
Pole Mount	Standard D35 mm
Stage Monitor Use Angle	45° - 25°
Speaker Dimension (WxHxD)	275 x 420 x 250mm

Packing Dimension (WxHxD)	300 x 460 x 283mm
Net Weight	7.0 kg
Gross Weight	8.0 kg